







# **SPECIFICATIONS**

Panel Resolution3440 x 1440 (UWQHD)Refresh Rate144HzResponse timeIms(MPRT)DYNAMIC REFRESH RATE TECHNOLOGYAdaptive-SyncPanel TypeVABrightness (nits)300Yiewing Angle178°(H)/178°(V)Aspect Ratio21:9Curvature1500RContrast Ratio4000:1DCR100000000:1Pixel Pitch (H x V)0.23175(H) x 0.23175 (V)Surface TreatmentAnti-glareDisplay Colors1.07B(8 bits + FRC)DCI-P3 / sRGB92.57% / 118.25%Video ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42ASignal Frequency30~160 KHz(H) 60 to 144Hz(V)Adjustment (Tilt)-5° ~ 20°Adjustment (Fivot)-5° ~ 5°Adjustment (Height)0 - 90mmDimension (W x H x D)810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inchCarton Dimension (W X H X D)6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbsFrameless DesignYes	Panel Size	34" (86.36 cm)
Response timeIms(MPRT)DYNAMIC REFRESH RATE TECHNOLOGYAdaptive-SyncPanel TypeVABrightness (nits)300Viewing Angle178°(H)/178°(V)Aspect Ratio21:9Curvature1500RContrast Ratio4000:1DCR100000000:1Pixel Pitch (H x V)0.23175(H) x 0.23175 (V)Surface TreatmentAnti-glareDisplay Colors1.078(8 bits + FRC)DCI-P3 / sRGB92.57% / 118.25%Video ports1 x DP (1.4) 2 x HDMI (2.0)Audio ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42ASignal Frequency30°-160 KHz(H) 60 to 144Hz(V)Adjustment (Tilt)-5° ~ 20°Adjustment (Pivot)-5° ~ 5°Adjustment (Height)0 - 90mmDimension (W x H x D)910 x 210 x 485 mm / 31.89 x 10.63 x 20.04 lbsWeight (NW / GW)6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Panel Resolution	3440 x 1440 (UWQHD)
DYNAMIC REFRESH RATE TECHNOLOGYAdaptive-SyncPanel TypeVABrightness (nits)300Viewing Angle178°(H)/178°(V)Aspect Ratio21:9Curvature1500RContrast Ratio4000:1DCR100000000:1Pixel Pitch (H x V)0.23175(H) x 0.23175 (V)Surface TreatmentAnti-glareDisplay Colors1.078(8 bits + FRC)DCI-P3 / sRGB92.57% / 118.25%Video ports1 x DP (1.4) 2 x HDMI (2.0)Audio ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42APower Input19V 3.42ASignal Frequency30°-160 KHz(H) 60 to 144Hz(V)Adjustment (Tilt)-5° ~ 20°Adjustment (Pivot)-5° ~ 5°Adjustment (Height)0 - 90mmDimension (W x H x D)910 x 210 x 485 mm / 31.89 x 10.63 x 20.08 inchWeight (NW / GW)6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Refresh Rate	144Hz
TECHNOLOGY         Adaptive-Sync           Panel Type         VA           Brightness (nits)         300           Viewing Angle         178°(H)/178°(V)           Aspect Ratio         21:9           Curvature         1500R           Contrast Ratio         4000:1           DCR         100000000:1           Pixel Pitch (H x V)         0.23175(H) x 0.23175 (V)           Surface Treatment         Anti-glare           Display Colors         1.07B(8 bits + FRC)           DCI-P3 / sRGB         92.57% / 118.25%           Video ports         1x DP (1.4)           Autio ports         1 x Earphone out           Kensington Lock         Yes           VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Signal Frequency         30° ~ 160 KHz(H)           60 to 144Hz(V)         Adjustment (Tilt)           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Response time	1ms(MPRT)
Brightness (nits)         300           Viewing Angle         178°(H)/178°(V)           Aspect Ratio         21:9           Curvature         1500R           Contrast Ratio         4000:1           DCR         100000000:1           Pixel Pitch (H x V)         0.23175(H) x 0.23175 (V)           Surface Treatment         Anti-glare           Display Colors         1.07B(8 bits + FRC)           DCI-P3 / sRGB         92.57% / 118.25%           Video ports         1 x Earphone out           Kensington Lock         Yes           VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs		Adaptive-Sync
Viewing Angle $178^{\circ}(H)/178^{\circ}(V)$ Aspect Ratio $21:9$ Curvature $1500R$ Contrast Ratio $4000:1$ DCR $100000000:1$ Pixel Pitch (H x V) $0.23175(H) \times 0.23175(V)$ Surface Treatment       Anti-glare         Display Colors $1.078(8 bits + FRC)$ DCI-P3 / sRGB $92.57\%/118.25\%$ Video ports $1x DP(1.4)$ Zx HDMI (2.0) $1x Earphone out$ Kensington Lock       Yes         VESA Mounting $75 \times 75 mm$ Power Type       External Adaptor 19V 3.42A         Signal Frequency $30\sim-160 \text{ KHz(H)}$ $60 \text{ to 144Hz(V)}$ $342A$ Adjustment (Tilt) $-5^{\circ} \sim 20^{\circ}$ Adjustment (Fivot) $-5^{\circ} \sim 5^{\circ}$ Adjustment (Pivot) $-5^{\circ} \sim 5^{\circ}$ Dimension (W x H x D) $910 \times 210 \times 485 mm / 31.89 \times 10.63 \times 20.08 inch$ Weight (NW / GW) $6.91 \log / 9.36 \log 15.24 \ln bs / 20.64 \ln bs$	Panel Type	VA
Aspect Ratio         21:9           Curvature         1500R           Contrast Ratio         4000:1           DCR         100000000:1           Pixel Pitch (H x V)         0.23175(H) x 0.23175 (V)           Surface Treatment         Anti-glare           Display Colors         1.078(8 bits + FRC)           DCI-P3 / sRGB         92.57% / 118.25%           Video ports         1 x DP (1.4)           2x HDMI (2.0)         Audio ports           Audio ports         1 x Earphone out           Kensington Lock         Yes           VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Power Input         19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Fivot)         -5° ~ 5°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Brightness (nits)	300
Curvature         1500R           Contrast Ratio         4000:1           DCR         100000000:1           Pixel Pitch (H x V)         0.23175(H) x 0.23175 (V)           Surface Treatment         Anti-glare           Display Colors         1.078(8 bits + FRC)           DCI-P3 / sRGB         92.57% / 118.25%           Video ports         1 x DP (1.4)           2x HDMI (2.0)         Audio ports           Audio ports         1 x Earphone out           Kensington Lock         Yes           VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Power Input         19V 3.42A           Signal Frequency         30~160 KHz(H)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Fivot)         -5° ~ 5°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Viewing Angle	178°(H)/178°(V)
Contrast Ratio         4000:1           DCR         10000000:1           Pixel Pitch (H x V)         0.23175(H) x 0.23175 (V)           Surface Treatment         Anti-glare           Display Colors         1.07B(8 bits + FRC)           DCI-P3 / sRGB         92.57% / 118.25%           Video ports         1x DP (1.4) 2x HDMI (2.0)           Audio ports         1 x Earphone out           Kensington Lock         Yes           VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Aspect Ratio	21:9
DCR         10000000:1           Pixel Pitch (H x V)         0.23175(H) x 0.23175 (V)           Surface Treatment         Anti-glare           Display Colors         1.07B(8 bits + FRC)           DCI-P3 / sRGB         92.57% / 118.25%           Video ports         1x DP (1.4) 2x HDMI (2.0)           Audio ports         1 x Earphone out           Kensington Lock         Yes           VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Power Input         19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Quos inch         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Curvature	1500R
Pixel Pitch (H x V) $0.23175(H) \times 0.23175(V)$ Surface Treatment       Anti-glare         Display Colors $1.078(8 bits + FRC)$ DCI-P3 / sRGB $92.57\% / 118.25\%$ Video ports $1 \times DP(1.4)$ Audio ports $1 \times Earphone out$ Kensington Lock       Yes         VESA Mounting $75 \times 75 mm$ Power Type       External Adaptor 19V 3.42A         Signal Frequency $30 \sim 160 \text{ KHz(H)}$ Adjustment (Tilt) $-5^{\circ} \sim 20^{\circ}$ Adjustment (Pivot) $-5^{\circ} \sim 5^{\circ}$ Adjustment (Height) $0 - 90mm$ Dimension (W x H x D) $810 \times 270 \times 510 mm / 31.89 \times 10.63 \times 20.08 inch$ Carton Dimension (W X H X D) $910 \times 210 \times 485 mm / 35.83 \times 8.27 \times 19.09 inch$ Weight (NW / GW) $6.91 \text{ kg } / 9.36 \text{ kg} \times 20.64 \text{ lbs}$	Contrast Ratio	4000:1
Surface TreatmentAnti-glareDisplay Colors $1.07B(8 bits + FRC)$ DCI-P3 / sRGB $92.57\% / 118.25\%$ Video ports $1x DP (1.4)$ $2x HDMI (2.0)$ Audio ports $1 x Earphone out$ Kensington LockYesVESA Mounting $75 x 75 mm$ Power TypeExternal Adaptor 19V 3.42APower Input $19V 3.42A$ Signal Frequency $30 \sim 160 \text{ KHz(H)}$ $60 to 144Hz(V)$ Adjustment (Tilt) $-5^{\circ} \sim 20^{\circ}$ Adjustment (Pivot) $-5^{\circ} \sim 5^{\circ}$ Adjustment (Height) $0 - 90mm$ Dimension (W x H x D) $810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch$ Weight (NW / GW) $6.91 \text{ kg } / 9.36 \text{ kg}$ $15.24 \text{ lbs } / 20.64 \text{ lbs}$	DCR	10000000:1
Display Colors1.07B(8 bits + FRC)DCI-P3 / sRGB92.57% / 118.25%Video ports1x DP (1.4) 2x HDMI (2.0)Audio ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42APower Input19V 3.42ASignal Frequency30~160 KHz(H) 60 to 144Hz(V)Adjustment (Tilt)-5° ~ 20°Adjustment (Swivel)-30° ~ 30°Adjustment (Height)0 - 90mmDimension (W x H x D)810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inchWeight (NW / GW)6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Pixel Pitch (H x V)	0.23175(H) x 0.23175 (V)
DCI-P3 / sRGB         92.57% / 118.25%           Video ports         1x DP (1.4) 2x HDMI (2.0)           Audio ports         1 x Earphone out           Kensington Lock         Yes           VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Power Input         19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Surface Treatment	Anti-glare
Video ports $1x DP (1.4)$ $2x HDMI (2.0)$ Audio ports $1 \times Earphone out$ Kensington LockYesVESA Mounting $75 \times 75 mm$ Power TypeExternal Adaptor 19V 3.42APower Input $19V 3.42A$ Signal Frequency $30 \sim 160 \text{ KHz(H)}$ $60 \text{ to } 144 \text{Hz(V)}$ Adjustment (Tilt) $-5^{\circ} \sim 20^{\circ}$ Adjustment (Swivel) $-30^{\circ} \sim 30^{\circ}$ Adjustment (Pivot) $-5^{\circ} \sim 5^{\circ}$ Adjustment (Height) $0 - 90mm$ Dimension (W x H x D) $810 \times 270 \times 510 mm / 31.89 \times 10.63 \times 20.08 inch$ Carton Dimension (W X H X D) $910 \times 210 \times 485 mm / 35.83 \times 8.27 \times 19.09 inch$ Weight (NW / GW) $6.91 \text{ kg } / 9.36 \text{ kg} \\ 15.24 \text{ lbs } / 20.64 \text{ lbs}$	Display Colors	1.07B(8 bits + FRC)
Video ports       2x HDMI (2.0)         Audio ports       1 x Earphone out         Kensington Lock       Yes         VESA Mounting       75 x 75 mm         Power Type       External Adaptor 19V 3.42A         Power Input       19V 3.42A         Signal Frequency       30~160 KHz(H) 60 to 144Hz(V)         Adjustment (Tilt)       -5° ~ 20°         Adjustment (Swivel)       -30° ~ 30°         Adjustment (Pivot)       -5° ~ 5°         Adjustment (Height)       0 - 90mm         Dimension (W x H x D)       810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch         Carton Dimension (W X H X D)       910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch         Weight (NW / GW)       6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	DCI-P3 / sRGB	92.57% / 118.25%
Kensington Lock         Yes           VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Power Input         19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Video ports	
VESA Mounting         75 x 75 mm           Power Type         External Adaptor 19V 3.42A           Power Input         19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Audio ports	1 x Earphone out
Power Type         External Adaptor 19V 3.42A           Power Input         19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Kensington Lock	Yes
Power Input         19V 3.42A           Signal Frequency         30~160 KHz(H) 60 to 144Hz(V)           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -5° ~ 5°           Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	VESA Mounting	75 x 75 mm
Signal Frequency $30 \sim 160 \text{ KHz(H)} \\ 60 \text{ to } 144\text{Hz(V)}$ Adjustment (Tilt) $-5^{\circ} \sim 20^{\circ}$ Adjustment (Swivel) $-30^{\circ} \sim 30^{\circ}$ Adjustment (Pivot) $-5^{\circ} \sim 5^{\circ}$ Adjustment (Height) $0 - 90\text{mm}$ Dimension (W x H x D) $810 \times 270 \times 510 \text{ mm } / 31.89 \times 10.63 \times 20.08 \text{ inch}$ Carton Dimension (W X H X D) $910 \times 210 \times 485 \text{ mm } / 35.83 \times 8.27 \times 19.09 \text{ inch}$ Weight (NW / GW) $6.91 \text{ kg } / 9.36 \text{ kg} \times 15.24 \text{ lbs } / 20.64 \text{ lbs}$	Power Type	External Adaptor 19V 3.42A
Signal Frequency       60 to 144Hz(V)         Adjustment (Tilt)       -5° ~ 20°         Adjustment (Swivel)       -30° ~ 30°         Adjustment (Pivot)       -5° ~ 5°         Adjustment (Height)       0 - 90mm         Dimension (W x H x D)       810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch         Carton Dimension (W X H X D)       910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch         Weight (NW / GW)       6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Power Input	19V 3.42A
Adjustment (Swivel)       -30° ~ 30°         Adjustment (Pivot)       -5° ~ 5°         Adjustment (Height)       0 - 90mm         Dimension (W x H x D)       810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch         Carton Dimension (W X H X D)       910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch         Weight (NW / GW)       6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Signal Frequency	
Adjustment (Pivot)       -5° ~ 5°         Adjustment (Height)       0 - 90mm         Dimension (W x H x D)       810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch         Carton Dimension (W X H X D)       910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch         Weight (NW / GW)       6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Adjustment (Tilt)	-5° ~ 20°
Adjustment (Height)         0 - 90mm           Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Adjustment (Swivel)	-30° ~ 30°
Dimension (W x H x D)         810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Adjustment (Pivot)	-5° ~ 5°
Dimension (W x H x D)         x 20.08 inch           Carton Dimension (W X H X D)         910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Adjustment (Height)	0 - 90mm
Carton Dimension (W X H X D)         19.09 inch           Weight (NW / GW)         6.91 kg / 9.36 kg           15.24 lbs / 20.64 lbs	Dimension (W x H x D)	· · · · · · · · · · · · · ·
15.24 lbs / 20.64 lbs	Carton Dimension (W X H X D)	
Frameless Design Yes	Weight (NW / GW)	
	Frameless Design	Yes

### FEATURES



N11/2

### Curved Gaming

GAMING MSI Curved Gaming Monitor will give you the most immersive and competitive edge you need to take down your opponents.

#### 144Hz High Refresh Rate

Experience smooth gaming with a blazing fast 144Hz refresh rate, that gives you the upperhand in fast moving games.

#### Fast Response Time

Eliminate screen tearing and choppy frame rates with 1ms GTG response time.

Wide Color Gamut

Wide Color Game colors and details will look more realistic and refined, to

#### UWQHD (3440 x 1440)

**UWQHD** <sub>3440 X 1440</sub> Game titles will even look better, displaying more details due to the WQHD (3440 x 1440) resolution.

### 1500R

**1500R** Enjoy the most immersive gameplay with 1500R curvature rate.





Optix MAG342CQR

SEE BEYOND THE GAME. VISUALIZE YOUR VICTORY.

Note

Display Port: 3440 x 1440 (Up to 144Hz) HDMI: 3440 x 1440 (Up to 100Hz) sRGB and DCI-P3 follow CIE1976 standrard

## **CONNECTIONS**



